

SIMPLE 220 Volt

INTONACATRICE - PLASTER SPRAYER

PER INTONACI GIÀ MESCOLATI - TRADIZIONALI
PREMISCELATI - FINITURE - INIEZIONI - FUGATURE

FOR FINISHING PLASTER
INJECTION FOR LEAK - TRADITIONAL PLASTER - PRE-MIXED



DIMENSIONI	
LARGHEZZA	cm 75
LUNGHEZZA	cm 150
ALTEZZA	cm 67
PESO	Kg. 138

DIMENSIONS	
WIDTH	cm 75
LENGTH	cm 150
HEIGHT	cm 67
WEIGHT	Kg. 138

DIMENSIONS	
LARGEUR	cm 75
LONGUEUR	cm 150
HAUTEUR	cm 67
POIDS	Kg. 138

DOTAZIONE	EQUIPMENT	DOTATION	AUSRÜSTUNG
Tubo 15 m.	15 mt. pipe	Tuyau de 15 m.	15 N. Rohr
Pistola intonaco	Mortar gun	Pistole pour enduit	Verputzpistole
Compressore	Compressor	Compresseur	Kompressor
Prolunga tensione	Voltage extension	Prolongateur de tension	Spannungsverlängerungsschnur
Vaglio vibrante	Vibrating screen	Temis vibrant	Vibrierendes Sieb

PRESTAZIONI	PERFORMANCES	PRESTATIONS	LEISTUNGEN
Da 0 a 20 l. min/max dipende dal materiale	From min. 0 to max. 20 lt. according to the kind of material	Du min. de 0 au max. de 20 l. selon le type de matériel	Vom 0 bis 20 L., es hängt dem Material ab.

GRANULOMETRIA	GRANULOMETRY	GRANULOMÉTRIE	GRANULOMETRIE
Da 0 a 6 mm.	From 0 to 6 mm.	De 0 a 6 mm.	Ab 0 bis 6 MM

PREVALENZA	HEAD	PRÉVALENCE	FÖRDERHÖHE
10-15 m.	10-15 mt.	10-15 m.	10-15 M.

Distanza tubo massima 30 m. e materiali idonei
Max. 30 mt. distance and suitable materials
Distance tuyau max. 30 m. et matériaux appropriés
Max. Rohrsehtfernung 30 M. voll und geeigneten Materialien



Motore elettrico 3 Hp
Electric motor 3 Hp
Moteur électrique 3 Hp
Elektriske motor 3 Hp



OPTIONAL

